

## P6S Series Transient Voltage Suppressor Diode

### General Information

The P6S series is designed to protect voltage sensitive components from high voltage, high energy transients. They have excellent clamping capability, high surge capability, low zener impedance and fast response time. The P6S series is supplied in YINT Semiconductor's exclusive, cost-effective, highly reliable and is ideally suited for use in communication systems, automotive, numerical controls, process controls, medical equipment, business machines, power supplies and many other industrial/consumer Applications.



### Features

- P600 glass passivated chip junction
- Plastic package
- Polarity: Color band denoted positive end (cathode) except Bidirectional.
- Typical failure mode is short from over-specified voltage or current
- Fast response time: typically less than 1.0ps from 0 Volts to BV min.
- High Temperature soldering: 260° C/10 seconds at terminals.
- Solder dip 275 ° C max. 10 s, per JESD 22-B106

### Typical Applications

Use in sensitive electronics protection against voltage transients induced by inductive load switching and lighting on ICs, MOSFET, signal lines of sensor units for consumer, computer, industrial, automotive, and telecommunication.

### Electrical Characteristics (@ T<sub>A</sub> = 25° C Unless Otherwise Noted)

Parameter	Symbol	Value	Unit
Peak pulse power dissipation with a 10/1000 μs waveform	P <sub>PK</sub>	6000	Watts
Peak pulse current with a 10/1000 μs waveform	I <sub>FSM</sub>	See next table	Amps
Power dissipation on infinite heat sink at T <sub>L</sub> = 75 ° C	P <sub>D</sub>	8	Watts
Peak forward surge current 8.3 ms single half sine-wave	I <sub>FSM</sub>	400	Amps
Instantaneous forward voltage at 100 A for Unidirectional only	V <sub>F</sub>	3.5	V
Operating junction and storage temperature range	T <sub>J</sub> , T <sub>STG</sub>	-55 to +175	° C


Notes :

- (1) Non-repetitive current pulse, per fig. 6 and derated above T<sub>A</sub> = 25 ° C per fig. 2
- (2) Measured 8.3 ms single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum


### Electrical Characteristics

Part Number (Bi)	Part Number (Uni)	Reverse Stand off Voltage $V_R$ (Volts)	Breakdown Voltage $V_{BR}$ (Volts)@ $I_T$		Test Current $I_T$ (mA)	Maximum Reverse Leakage $I_R$ @ $V_R$ ( $\mu$ A)	Maximum Peak Pulse Current $I_{pp}$ (A)	Maximum Clamping Voltage $V_C$ @ $I_{pp}$ (V)
			Min .V	Max .V				
P6S15CA	P6S15A	15	16.7	18.5	5	2	245.9	24.4
P6S18CA	P6S18A	18.0	20.0	22.1	5	2	205.4	29.2
P6S24CA	P6S24A	24.0	26.7	29.5	5	2	254.2	38.9
P6S33CA	P6S33A	33.0	36.70	40.60	5	2	106.5	56.3
P6S36CA	P6S36A	36.0	40.0	44.2	5	2	103.2	58.1

Functional Diagram



I-V Curve Characteristics



Symbol	Parameter
$I_{PP}$	Maximum Reverse Peak Pulse Current
$V_C$	Clamping Voltage @ $I_{PP}$
$V_{RWM}$	Working Peak Reverse Voltage
$I_R$	Maximum Reverse Leakage Current @ $V_{RWM}$
$V_{BR}$	Breakdown Voltage @ $I_T$
$I_T$	Test Current

Rating & Characteristic Curves

Figure 1 - Peak Pulse Power Rating Curve




Figure 2 - Pulse Derating Curve




Figure 3 - Pulse Waveform




Figure 4 - Typical Junction Capacitance




Figure 5 - Pulse Derating Curve






Figure 6 - Maximum Non-Repetitive Surge Current





**Disclaimer**

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.

Users should verify actual device performance in their specific applications.